

RWE

SIMEX
HEAVY MADE EASY



simex.it



RWE 60



For excavator boom mounting, RWE 60 wheel saws are designed to make set-section cuts on hard and compact surfaces: asphalt, concrete, rock.

Ideal for demolition and underwater works. Two high-displacement radial piston hydraulic motors in direct drive guarantee a high torque.

SIMEX **PERFORMER**
• patent •



ADVANTAGES

- Ideal for demolition
- Can work under water
- High performance
- High cutting force

TECHNICAL DATA

RWE 60

TECHNICAL DATA		RWE 60
Recommended excavator weight (1)	ton lbs	28 - 45 61000 - 99000
Width	mm inch	100 - 130 - 200 4 - 5 - 8
Depth	mm inch	600 24
Cutting force	kN lbf	23 5170
Operating weight (2)	kg lbs	2550 5600
Required oil flow	l/min gpm	200 - 350 53 - 93
Max. required oil pressure	BAR psi	350 5100

(1) User is responsible for ensuring that the equipment meets the excavator's specifications and weight requirements.

(2) Without mounting bracket attaching to prime mover.

Simex does not accept responsibility or liability for the information provided. Technical modifications may vary without prior notice.



Utilities



Quarries and mines



Demolition



Port and underwater works



Construction and building



Infrastructure



Tunneling



Agriculture and forestry



Recycling



Roadworks



Trenching



Mini-excavator



Excavator



Skid steer loader



Front loader



Backhoe